



LFD-6

Large Figure Display

The LFD-6 remote display unit has been designed mainly for use on hydrant dispensers and aviation refuellers working at airports.

This application requires the volume measured by the PD meter be repeated and easily read from a reasonable distance within the working area.

The LFD-6 nevertheless can be used in any application where the operator is working at a distance from the meter counter and an easily readable display is required. Such typical applications include top loading of tank trucks and rail cars, also loading of barges, ships, etc.



The displayed value is get by factorised pulses representing the minimum value to be read (e.g. if the display is required in litres, then 1 pulse=litre).

The LFD-6 has a maximum of 6 digits plus a decimal point that can be programmed in a fixed position. At the end of the delivery the unit can be reset to zero remotely by means of a dedicated input.

If the LFD-6 is used in conjunction with ISOIL's VEGAll or VEGAT electronic counter it can be linked via serial line. In this case up or down counting can be done.

The display brightness is achieved by automatic, self adjusting LED which provides very high readability in all lighting conditions

The peculiarity of LFD-6 is to be suitable for use in explosive areas and harsh environments. ATEX conformity and IP66 protection rating.

www.isoilmeter.com



LFD6 on terminal application

From a metrological viewpoint, it is the main meter (and counter) that is the only official metering reference. Therefore, the LFD-6 has to be considered as a simple repeater of the main instrument.



LFD6 on hydrant dispenser

Technical specifications

| | |
|--------------------------|--|
| Reading | N° 6 digit 63(H)x30(L) mm- Red L.E.D. high efficiency type+decimal point |
| Brightness | Self adjusting according to the environmental conditions |
| Unit of measure | At custom choice by means of labels with the main units of measure |
| Counting input | From npn/ pnp open collector transistor or square wave 5-15VDC – 5KHz max |
| Reset input | From npn/ pnp open collector transistor or square wave 5-15VDC – 5KHz max |
| Serial communication | N° 1 line settable as RS232 or RS485 (communication protocol compatible with ISOIL VEGAll e VEGA T electronic registers) |
| Mains | 10-30VDC |
| Power | 10 W max |
| Working temperature | -25÷55°C |
| Stock temperature | -40÷65°C |
| Relative humidity: | 0÷95% without condensation |
| Housing's material | Anodised alluminium alloy |
| Environmental protection | IP66 |
| ATEX conformity | For category II 2 G protection mode Ex-d IIB T6 EC type examination certificate INERIS 08ATEX0028 |
| Cable entries (standard) | 2 holes 1/2" NPT on bottom side |
| Cable clamps | In the bottom side, spring terminals for wires 1,5mmq max |
| Mounting facilities | N° 6 screwed holes M6x10 on the back and lateral sides for wall or bracket mounting Equipped with silent block supports |
| Dimensions /Weight | 388x148x49mm / 5 Kg |
| Reading | N° 6 digit 63(H)x30(L) mm- Red L.E.D. high efficiency type+decimal point |

